

Package: geoperu (via r-universe)

October 8, 2024

Title Download Spatial Datasets of Peru

Version 0.0.0.2

Description Provides convenient access to the official spatial datasets of Peru as 'sf' objects in R. This package includes a wide range of geospatial data covering various aspects of Peruvian geography, such as: administrative divisions (Source: INEI <<https://ide.inei.gob.pe/>>), protected natural areas (Source: GEO ANP - SERNANP <<https://geo.sernanp.gob.pe/visorsernanp/>>). All datasets are harmonized in terms of attributes, projection, and topology, ensuring consistency and ease of use for spatial analysis and visualization.

License MIT + file LICENSE

Suggests testthat (>= 3.0.0)

Config/testthat/edition 3

Encoding UTF-8

Roxygen list(markdown = TRUE)

RoxygenNote 7.3.2

BugReports <https://github.com/PaulESantos/geoperu/issues>

Depends R (>= 3.6.0)

LazyDataCompression xz

LazyData true

URL <https://github.com/PaulESantos/geoperu>,
<https://paulesantos.github.io/geoperu/>

Imports curl, data.table, httr, methods, sf

Repository <https://paulesantos.r-universe.dev>

RemoteUrl <https://github.com/paulesantos/geoperu>

RemoteRef HEAD

RemoteSha 69b9e1dfc6f560f75821a356de03630101089767

Contents

get_anp_peru	2
get_geo_peru	3
peru	4
Index	5

get_anp_peru	<i>Download Spatial Data of Protected Natural Areas (ANP) in Peru</i>
--------------	---

Description

Downloads spatial data of protected natural areas in Peru declared by SERNAP (National Service of Natural Protected Areas). Data were obtained from **GEO ANP** as the official source. The data are in the "WGRS84" reference system and CRS(4326).

Usage

```
get_anp_peru(anp = NULL, showProgress = TRUE)
```

Arguments

anp	A character or a vector with the name(s) of the protected natural areas in Peru.
showProgress	Logical TRUE or FALSE to display a progress bar during download.

Value

An "sf" "data.frame" object containing the spatial data of Peru's protected natural areas.

Examples

```
# Read specific ANP
manu <- get_anp_peru(anp = "Manu")

pampa_galeras <- get_anp_peru(anp = "Pampa Galeras")

# Read more than one ANP
anps <- get_anp_peru(anp = c("Manu", "Yanachaga", "Calipuy"))
```

get_geo_peru	<i>Download spatial data of Peru</i>
--------------	--------------------------------------

Description

Downloads spatial data of Peru using Geodetic reference system "WGRS84" and CRS(4326).

Usage

```
get_geo_peru(  
  geography = "all",  
  level = "all",  
  simplified = TRUE,  
  showProgress = TRUE  
)
```

Arguments

geography	A character or a vector with the name of geographical region. An exception is "all" to request all Peru data.
level	A character: "all" for national level data, "dep" for department level data, and "prov" for provincial level data.
simplified	A logical TRUE or FALSE, to select data with all districts or a polygon simplified to a higher level.
showProgress	Logical TRUE or FALSE to display a progress bar during download.

Value

An "sf" "data.frame" object containing the spatial data of Peru.

Examples

```
# Read specific province  
anta <- get_geo_peru(geography = "ANTA",  
                    level = "prov",  
                    simplified = TRUE)  
  
# Read more than one province  
df <- get_geo_peru(geography = c("CALCA"),  
                  level = "prov",  
                  simplified = FALSE)  
  
# Read department level data  
cusco <- get_geo_peru(geography = "cusco",  
                     level = "dep",  
                     simplified = TRUE)
```

peru

Districts Peru

Description

Información geográfica vectorial de los 1722 distritos del PERU y su geometría.

Usage

peru

Format

A SpatialPolygonsDataFrame

Source

<https://ide.inei.gob.pe/>

Index

* **dataset**

peru, 4

get_anp_peru, 2

get_geo_peru, 3

peru, 4